

# MCT36

Trowels



**WACKER  
NEUSON**  
*all it takes!*



## Perfect concrete finishing results: MCT36

The M-series MCT36 Walk-behind Trowel is ideal for areas less than 500 square meters reducing the time required to finish the job. This trowel is optimally balanced and can be effortlessly controlled in a wide range of speeds. The MCT36 Walk-behind Trowel will make your process more efficient and improve the concrete surface finish.

- Equipped with height adjustable "whale tail" trowel handle for ergonomic operation.
- Powered with reliable and powerful four stroke gasoline engine.
- Variable speeds: lower speeds for floating, higher speeds for finishing.
- Throttle control located on the handle for adjusting blade speed.
- Integrated lift point for job site maneuvering.

## MCT36 Technical specifications

L x W x H	1820 x 945 x 980 mm
Weight	83 kg
Troweling diameter	915 mm
Pitch range	0 - 15 °
Rotor speed (min. / max.)	70/137 rpm
Quantity of blades	4
Engine / Motor	Air-cooled, single-cylinder four-cycle gasoline engine
Engine / Motor manufacturer	Loncin
Engine / Motor type	G200F
Displacement	196 cm <sup>3</sup>
Engine performance @ 3,600 rpm	4.1 (5.5) kW (hp)
at rpm	3,600 rpm
Fuel consumption	1.2 l/h
Fuel tank capacity	3.6 l
Tank capacity (engine oil)	0.6 l

Please note: that product availability can vary from country to country. It is possible that information / products may not be available in your country. More detailed information on engine power can be found in the operator's manual; the stated power may vary due to specific operating conditions. Subject to alterations and errors excepted. Applicable also to illustrations.  
Copyright © 2019 Wacker Neuson SE.